

Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the application.

Claim 1 (currently amended): A computer readable medium having a dictionary comprising codevectors of variable dimension stored thereon, said dictionary being and intended to be used in a device for at least one of compression coding and ~~for~~ decoding of digital signals, by vector quantization at variable rate defining a variable resolution, wherein the dictionary comprises:

- ~~on the one hand, for a given dimension,~~ inter-embedded sub-dictionaries of increasing resolution of a given dimension,
- and, ~~on the other hand, for a given dimension,~~ wherein each sub-dictionary comprises a union:
 - of a first set consisting of codevectors constructed by inserting, into codevectors of dictionaries of lower dimension, elements taken from a finite set of real numbers according to a finite collection of predetermined insertion rules,
 - and of a second set consisting of codevectors that may not be obtained by insertion into codevectors of lower dimension of the elements of said finite set according to said collection of insertion rules.

Claim 2 (current amended): The computer readable medium dictionary as claimed in claim 1, wherein said collection of insertion rules is formulated on the basis of elementary rules consisting in inserting a single element of the finite set of real numbers in the guise of component at a given position of a vector.

Claim 3 (currently amended): The computer readable medium dictionary as claimed in claim 2, wherein each elementary rule is defined by a pair of two positive integers representative:

- of a rank of the element in said finite set,
- and of a position of insertion.

Claim 4 (currently amended): A method for forming a dictionary comprising codevectors of

variable dimension and intended to be used in a device for compression coding and/or decoding of digital signals, by vector quantization at variable rate defining a variable resolution,

in which, for a given dimension:

- a) a first set consisting of codevectors formed by performing an editing operation comprising at least one of inserting into and deleting from ~~inserting/deleting into/from~~ codevectors of dictionaries of ~~lower/higher~~ dimension elements comprising at least one of lower and higher dimension elements taken from a finite set of real numbers according to a finite collection of predetermined editing operation ~~insertion/deletion~~ rules,
- b) a first, intermediate, dictionary comprising at least said first set is constructed, for said given dimension,
- c) and, to adapt said dictionary to a use with at least one given resolution, a second, definitive, dictionary is constructed, on the basis of the intermediate dictionary, by performing at least one of embedding and ~~and~~ simplication of dictionaries of at least one of increasing and ~~and~~ decreasing resolutions, the dictionaries of increasing resolutions being inter-embedded from the dictionary of smallest resolution up to the dictionary of greatest resolution.

Claim 5 (currently amended): The method as claimed in claim 4, in which, for a given dimension N :

- a0) an initial dictionary of initial dimension n , lower than said given dimension N , is obtained,
- a1) a first set consisting of codevectors of dimension $n+i$, with i being a non negative integer, formed by inserting into codevectors of the initial dictionary elements taken from a finite set of real numbers according to a finite collection of predetermined insertion rules is constructed,
- a2) there is provided a second set consisting of codevectors of dimension $n+i$ that may not be obtained by insertion into the codevectors of the initial dictionary of the elements of said finite set with said collection of insertion rules,
- a3) an intermediate dictionary, of dimension $n+i$ comprising a union of said first set and of said second set is constructed,

and steps a1) to a3) are repeated, at most $N-n-1$ times, with said intermediate dictionary in the guise of initial dictionary, up to said given dimension N .

Claim 6 (currently amended): A method for forming a dictionary comprising codevectors of variable dimension and intended to be used in a device for compression coding and/or decoding of digital signals, by vector quantization at variable rate defining a variable resolution,

in which, for a given dimension:

- a) a first set consisting of codevectors formed by performing an editing operation comprising at least one of inserting into and deleting from codevectors of dictionaries of dimension elements comprising at least one of lower and higher dimension elements taken from a finite set of real numbers according to a finite collection of predetermined editing operation rules,
- b) a first, intermediate, dictionary comprising at least said first set is constructed, for said given dimension,
- c) and, to adapt said dictionary to a use with at least one given resolution, a second, definitive, dictionary is constructed, on the basis of the intermediate dictionary, by performing at least one of embedding and simplification of dictionaries of at least one of increasing and decreasing resolutions, the dictionaries of increasing resolutions being inter-embedded from the dictionary of smallest resolution up to the dictionary of greatest resolution;

~~The method as claimed in claim 4,~~ in which, for a given dimension N :

- a'0) an initial dictionary of initial dimension n , higher than said given dimension N , is obtained,
- a'1) a first set, of dimension $n-i$, with i being a non negative integer, is constructed by selection and extraction of possible codevectors of dimension $n-i$ from the dictionary of dimension n , according to a finite collection of predetermined deletion rules,
- a'2) there is provided a second set consisting of codevectors of dimension $n-i$, that may not be obtained by deletion, from the codevectors of the initial dictionary, of the elements of said finite set with said collection of deletion rules,

a'3) an intermediate dictionary, of dimension $n-i$ comprising a union of said first set and of said second set is constructed,
and steps a'1) to a'3) are repeated, at most $n-N+1$ times, with said intermediate dictionary in the guise of initial dictionary, ~~down up~~ to said given dimension N .

Claim 7 (currently amended): The method as claimed in claim 5, in which N successive dictionaries of respective dimensions 1 to N are obtained on the basis of an initial dictionary of dimension $n-p$, through the repeated implementation of steps a1) to a3) for the dimensions $n-p+1$ to N , and through the repeated implementation of steps a'1) to a'3) for the dimensions $n-p-1$ to 1 .

Claim 8 (currently amended): The method as claimed in claim 4, in which said collection of editing operation ~~insertion/deletion~~ rules is formulated on the basis of elementary rules consisting in performing the editing operation on ~~inserting/deleting~~ a single element of the finite set of reals in the guise of component at a given position of a vector.

Claim 9 (currently amended): The method as claimed in claim 8, in which each elementary rule is defined by a pair of two positive integers representative:

- of a rank of the element in said finite set,
- and of a position of the editing operation ~~insertion/deletion~~.

Claim 10 (currently amended): The method as claimed in claim 4, in which said finite set and said collection of editing operation ~~insertion/deletion~~ rules are defined a priori, before constructing the dictionary by analysis of a source to be quantized.

Claim 11 (currently amended): The method as claimed in claim 10, in which said source is modeled ~~modelled~~ by a learning sequence and the definition of said finite set and of said collection of editing operation ~~insertion/deletion~~ rules is effected by statistical analysis of said source.

Claim 12 (previously presented): The method as claimed in claim 10, in which said finite set

is chosen by estimation of a monodimensional probability density of said source.

Claim 13 (currently amended): The method as claimed in claim 4, in which said finite set and said collection of editing operation ~~insertion/deletion~~ rules are defined a posteriori after construction of dictionaries by performing at least one of embedding and / simplification of dictionaries of successive resolutions, followed by a statistical analysis of these dictionaries thus constructed.

Claim 14 (currently amended): The method as claimed in claim 10, in which:

- a first set and a first collection of editing operation ~~insertion/deletion~~ rules are chosen a priori by analysis of a learning sequence, so as to form one or more intermediate dictionaries,
- at least one part of said first set and/or of said first collection of editing operation ~~insertion/deletion~~ rules is updated by a posteriori analysis of said one or more intermediate dictionaries,
- and, as appropriate, at least one part of the set of codevectors forming said one or more intermediate dictionaries is also updated.

Claim 15 (currently amended): A method for forming a dictionary comprising codevectors of variable dimension and intended to be used in a device for compression coding and/or decoding of digital signals, by vector quantization at variable rate defining a variable resolution,
in which, for a given dimension:

- a) a first set consisting of codevectors formed by performing an editing operation comprising at least one of inserting and deleting on codevectors of dictionaries of dimension elements comprising at least one of lower and higher dimension elements taken from a finite set of real numbers according to a finite collection of predetermined editing operation rules,
- b) a first, intermediate, dictionary comprising at least said first set is constructed, for said given dimension,
- c) and, to adapt said dictionary to a use with at least one given resolution, a second, definitive, dictionary is constructed, on the basis of the intermediate dictionary, by

performing at least one of embedding and simplification of dictionaries of at least one of increasing and decreasing resolutions, the dictionaries of increasing resolutions being inter-embedded from the dictionary of smallest resolution up to the dictionary of greatest resolution; wherein

~~The method as claimed in claim 4, in which~~ step c) further comprises the following operations:

- c0) an initial dictionary of initial resolution r_n , lower than said given resolution r_N , is obtained,
- c1) on the basis of the initial dictionary, an intermediate dictionary of resolution r_{n+1} higher than the initial resolution r_n is constructed,
- c2) operation c1) is repeated until the given resolution r_N is attained.

Claim 16 (original): The method as claimed in claim 15, in which, for each iteration of operation c1), there is provided a construction of classes and of centroids, in which the centroids belonging at least to the dictionaries of resolution higher than a current resolution r_i are recalculated and updated.

Claim 17 (original): The method as claimed in claim 16, in which the centroids which belong to the dictionaries of resolution lower than a current resolution r_i are updated only if the total distortions of all the dictionaries of lower resolution are decreasing from one update to the next.

Claim 18 (previously presented): The method as claimed in claim 4, in which step c) comprises the following operations:

- c'0) an initial dictionary of initial resolution r_n , higher than said given resolution r_N , is obtained,
- c'1) on the basis of the initial dictionary, an intermediate dictionary of resolution r_{n-1} lower than the initial resolution r_n , is constructed by partitioning of the initial dictionary into several subsets ordered according to a predetermined criterion, and
- c'2) operation c'1) is repeated until the given resolution r_N is attained.

Claim 19 (original): The method as claimed in claim 18, in which said predetermined criterion is chosen from among the cardinal of the subsets, an invoking of the subsets in a learning sequence, a contribution of the subsets to a total distortion or preferably to a decrease of this distortion.

Claim 20 (currently amended): The method as claimed in claim 18, in which said partition uses part at least of said editing operation ~~insertion/deletion~~ rules.

Claim 21 (previously presented): The method as claimed in claim 15, in which N successive dictionaries of respective resolutions r_1 to r_N are obtained on the basis of an initial dictionary of intermediate resolution r_n , by the repeated implementation of step c1) for the increasing resolutions r_{n+1} to r_N , and through the repeated implementation of step c'1) for the decreasing resolutions r_{n-1} to r_1 .

Claim 22 (currently amended): The method as claimed in claim 4, in which, to adapt said dictionary to a use with a given dimension N of codevectors, steps a), ~~and b)~~, ~~on the one hand~~, and step c), ~~on the other hand~~, are substantially inverted so that:

- in step c), a first, intermediate, dictionary still of dimension N' but of at least one of higher and / lower resolution r_N is constructed on the basis of an initial dictionary of resolution r_n and of dimension N' by performing at least one of embedding and / simplification of dictionaries of at least one of increasing and / decreasing resolutions, so as to substantially attain the resolution r_N of said first dictionary,
- in step a), to attain the given dimension N , a first set consisting of codevectors formed by performing an editing operation that is at least one of inserting into and deleting from inserting/deleting, into/from codevectors of the first dictionary of dimension N' at least one of lower and / higher than said given dimension N elements taken from a finite set of real numbers according to a finite collection of predetermined editing operation ~~insertion/deletion~~ rules is constructed,
- and, in step b), subsequent to a possible step of definitive adaptation to the resolution r_N , a second, definitive, dictionary comprising at least said first set is constructed for said given dimension N .

Claim 23 (currently amended): The method as claimed in claim 4, further comprising storing ~~in which there is stored~~ in a memory, ~~once and for all~~, said collection of editing operation ~~insertion/deletion~~ rules, each identified by an index (l_r), and, for a given dimension:

- said second set consisting of codevectors that may not be obtained by application of the editing operation ~~insertion/deletion~~ to codevectors of at least one of lower and / higher dimension than the given dimension according to said collection of editing operation ~~insertion/deletion~~ rules,

- as well as at least one correspondence table making it possible to reconstitute any codevector of the dictionary of given dimension, using the indices of the editing operation ~~insertion/deletion~~ rules and indices identifying elements of said second set, thereby making it possible to avoid the complete storage of the dictionary for said given dimension, by simply storing the elements of said second set and links in the correspondence table for access to these elements and to the associated editing operation ~~insertion/deletion~~ rules.

Claim 24 (currently amended): The method as claimed in claim 23, in which the correspondence tables are formulated previously, for each index (m^j) of a codevector (x^j) of the dictionary ($D^j_{N_j}$) of given dimension (j) that may be reconstructed on the basis of elements of current indices (m') in the second set of current dimension (j'), through a tabulation of three integer scalar values representing:

- a current dimension (j') of said second set,
- a current index (m') of an element of the second set, and
- an editing operation ~~insertion/deletion~~ rule index (l_r),

this editing operation ~~insertion/deletion~~ rule at least contributing to reconstitute said codevector (x_j) of the dictionary ($D^j_{N_j}$) of given dimension (j), by applying the insertion/deletion to the element of said current index (m') and of said current dimension (j').

Claim 25 (currently amended): A method ~~for~~ of using a dictionary in the compression coding or / decoding of digital signals, by vector quantization at variable rate defining a variable resolution, comprising:

searching for a codevector (x^j) which is the nearest neighbour of an input vector $y=(y_0, \dots, y_k, \dots, y_{j-1})$ in a dictionary (D_j^i) of given dimension (j),
~~said dictionary, of a given dimension, giving codevectors being reconstituted by using at least one correspondence table making it possible to reconstitute any codevector of the dictionary of said given dimension, using indices of a collection of editing operation ~~insertion/deletion~~ rules that are at least one of insertion and deletion rules and indices identifying elements of a set of codevectors that may not be obtained by application of the editing operation ~~insertion/deletion~~ to codevectors of at least one of lower or / higher dimension than the given dimension according to said collection of editing operation ~~insertion/deletion~~ rules,~~
~~in which a search is made for the codevector (x^j) which is the nearest neighbour of an input vector $y=(y_0, \dots, y_k, \dots, y_{j-1})$ in a dictionary (D_j^i) of given dimension (j),~~
 and further comprising the following steps:

- CO1) for a current index (m^j) of said codevector (x^j) sought, reconstitution at least partial of a codevector of index (m') corresponding to said current index (m^j), at least through the prior reading of the indices (j' , m' , l) appearing in the correspondence tables making it possible to formulate said dictionary,
- CO2) at least on coding, calculation of a distance between the input vector and the codevector reconstituted in step CO1),
- CO3) at least on coding, repetition of steps CO1) and CO2), for all the current indices in said dictionary,
- CO4) at least on coding, identification of the index (m_{\min}) of the codevector at least partially reconstituted whose distance (d_{\min}), calculated in the course of one of the iterations of step CO2), with the input vector is the smallest, and
- CO5) at least on decoding, determination of the nearest neighbour of the input vector (y) in the guise of codevector (x^j) whose index (m_{\min}) has been identified in step CO4).

Claim 26 (currently amended): The method as claimed in claim 25, in which step CO1), at least on decoding, comprises:

CO11) the reading, in the correspondence tables, of indices representative of links to said second set and to the editing operation ~~insertion/deletion~~ rules and including:

- the index of a current dimension of a subset of said second set,

- the current index of an element of said subset,
- and the index of the appropriate editing operation ~~insertion/deletion~~ rule for the construction of the codevector of the dictionary of given dimension, on the basis of said element,

CO12) the reading, in the subset identified by its current dimension, of said element identified by its current index,

CO13) the complete reconstitution of the codevector to said given dimension by applying to said element read in step CO12) the appropriate editing operation ~~insertion/deletion~~ rule identified by its index read in step CO11).

Claim 27 (currently amended): The method as claimed in claim 25, in which, on coding,
* step CO1) comprises:

CO11) the reading, in the correspondence tables, of indices representative of links to said second set and to the editing operation ~~insertion/deletion~~ rules and including:

- the index of a current dimension of a subset of said second set,
- the current index of an element of said subset,
- and the index of the appropriate editing operation ~~insertion/deletion~~ rule for the construction of the codevector of the dictionary of given dimension,

CO12) the reading, in the subset identified by its current dimension, of said element identified by its current index,

* in step CO2), said distance is calculated as a function of a distortion criterion estimated as a function of:

- the index of the editing operation ~~insertion/deletion~~ rule,
- and of the element of the subset identified by its current index,

thereby making it possible to only partially construct the codevector with said given dimension in step CO1), by reserving the complete reconstruction simply for decoding.

Claim 28 (currently amended): The method use as claimed in claim 25, in which there is provided furthermore a supplementary structuring property according to a union of permutation codes and utilizing an index of said union of permutation codes, and in which:

- CP1) on the basis of an input signal, an input vector $y=(y_0, \dots, y_k, \dots, y_{j-1})$ defined by its absolute vector $|y|=(|y_0|, \dots, |y_k|, \dots, |y_{j-1}|)$ and by a sign vector $\varepsilon=(\varepsilon_0, \dots, \varepsilon_k, \dots, \varepsilon_{j-1})$ with $\varepsilon_k=\pm 1$ is formed,
- CP2) the components of the vector $|y|$ are ranked by decreasing values, by permutation, to obtain a leader vector $|\tilde{y}|$,
- CP3) a nearest neighbour x^j of the leader vector $|\tilde{y}|$ is determined from among the leaders of the dictionary D_i^j of dimension j ,
- CP4) an index of the rank of said nearest neighbour x^j in the dictionary D_i^j is determined,
- CP5) and an effective value of at least one of coding and / decoding is applied to the input vector, which is dependent on said index determined in step CP4), on said permutation determined in step CP2) and on said sign vector determined in step CP1).

Claim 29 (currently amended): The method as claimed in claim 25, in which at least said correspondence tables are stored in a memory of a at least one of coding and / decoding devices.

Claim 30 (currently amended): A computer readable memory storing a computer program product intended to be stored in a memory of a processing unit, in particular of a computer or of a mobile terminal, or on a removable memory medium and intended to cooperate with a reader of the processing unit,

wherein it comprises instructions for implementing a the method for forming a dictionary comprising codevectors of variable dimension and intended to be used in a device for compression coding and/or decoding of digital signals, by vector quantization at variable rate defining a variable resolution,

in which, for a given dimension:

- a) ~~a first set consisting of codevectors formed by inserting/deleting into/from codevectors of dictionaries of lower/higher dimension elements taken from a finite set of real numbers according to a finite collection of predetermined insertion/deletion rules,~~
- b) ~~a first, intermediate, dictionary comprising at least said first set is constructed, for said given dimension,~~